



Technical data

Date	9/23/2025
Offer N.	---
Pump Type	JAM300


Client	EES GmbH	Reference	---
--------	----------	-----------	-----

Pump data

Pump body	Cast iron	Self-priming centrifugal pump for water supplies (even if mixed with gas) in small household systems, connected to autoclave tanks, for transferring liquids and emptying tanks; also used for gardening.
Motor bracket	Cast iron	
Impeller	Noryl or brass	
Mechanical seal	Ceramic-Graphite	
Motor shaft	Stainless steel AISI 416	
Liquid temperature	0°C +50°C	
Operating pressure	Max 8 bar	

P2		P1 (kW)		A		Q (m3/h - l/min)						
(HP)	(kW)	1~	3~	1~ 1x230V	3~ 3x400V	0	1.2	2.4	3.6	4.8	6	7.2
						0	20	40	60	80	100	120
						H (m)						
3	2,2	2,7	-	12,5	-	70	63.9	58.3	53.5	49.2	45.1	41.6

Technical Sheet



DIMENSIONS (mm)									DNA	DNM	PACKAGING (mm)			Kg
A	B	C	D	E	F	G	H1	H2			I	L	M	
269,6	167	608	203	165	220	231,5	175	220	1"1/2G	1"1/4G	638	230	255	38

Notes

The information may be subject to change without notice. It is always advisable to contact our commercial department in order to get further information about the products, their technical specifications and warranty conditions. The Company is expressly relieved of any liability for the purchasing of a product not in line with the customer's needs, if not consulted beforehand for a specific consultancy.



Working Curves

Pump type: JAM300


Curv n°:

JAM300

Date:

9/23/2025

Q (l/min) 100 | H (m) 42 | Power [kW] 2.15 | Efficiency % 34.23 | NPSH (m) 6.2



MEI ≥ 0.4 (regulation EU N. 547/2012)
Tolerances according to UNI ISO 9906 grade 3B